







SERIES 161 SLIDING WINDOW (NO J-CHANNEL)

- + Beautiful, true brick mould exterior frame perimeter
- + Aluminum-reinforced lock rail and meeting rails add strength
- + Tandem rollers ride easily along friction free glide channel
- + Integrated glide rail allows easy sash opening and closing
- + Available in XO or OX configurations (sliding panel on left or right)
- + Series 151 available with Integrated J-channel
- + Pre-punched nail fin simplifies installation

- Insulated glass panels featuring warm-edge spacer system
- + Fusion-welded frame and sash corners help prevent air and water infiltration
- + 2-lite and 3-lite configurations available
- + Half screen comes standard*
- + Jamb depth: 3.277"
- + Limited lifetime warranty



2-lite sliding window

CUSTOM Options

- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5%" or 3¼" flat, 5%" or 1" contoured, 1 ½" simulated divided lite (SDL), 5%" contoured valance grids available
- + Nine painted exterior colors (white interior only)

- + Paintable or stainable wood jamb extensions (4 %16" and 6 %16")
- + Factory mulling of twins, triples and factory shapes
- + Charcoal aluminum mesh screen*
- + Custom sizes available







www.atrium.com



Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory Sales Manager for details.







Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 'Screens are not meant to restrain a child from falling through an open window.

through an open window.

** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

**** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details. REV 11/23