



SERIES 700 CASEMENT

- **Series 705 Awning also available**
- Low-E glass with insulating Argon Gas provides additional efficiency
- Insulated glass panels with optimum thermal air space featuring Warm-Edge spacer system
- Beveled exterior offers cosmetic appeal
- Solid vinyl construction with all-welded frame and sash corners yields premium energy-efficient performance and advanced structural integrity
- Sash easily cranks open 90° for easy cleaning

- State-of-the-art hardware with single-lever, multipoint lock accommodates single vent widths up to 3'0"
- Low-profile aesthetic handle operates smoothly and folds into assembly cover so it will not interfere with window treatments
- Multi-seal weather stripping adds extra protection against air and water infiltration
- **Transferable limited lifetime warranty**
- **Lifetime glass breakage warranty**



Single Vent Casement

CUSTOM Options

- **Ultra Low-E glass with Argon Gas**
- 1 1/8" simulated divided lite (SDL) grid
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Nine exterior painted colors, three interior wood laminates, bronze exterior laminate
- Charcoal aluminum, Clear View and heavy duty screens*
- Factory mulling of twins, triples and architectural shapes
- Brass and brushed nickel locks
- 2" simulated meeting rail (on casement windows)
- Custom sizes available



Single Vent Awning



Scan to
experience
our website.

COLOR Options**



Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Ellison Territory Sales Manager for details.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

*Screens are not meant to restrain a child from falling through an open window.

**Printing process may affect color shown. Please refer to actual window sample when selecting colors.

***Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.