



## SERIES 8100 SLIDING WINDOW

- + **Insulated glass panels** with optimum thermal air space featuring a warm-edge spacer system
- + **Aluminum-reinforced** lock and meeting rails enhance structural integrity
- + **Tandem rollers** ride easily along friction free glide channel
- + **Integrated glide rail** for easy sash opening and closing
- + **Available in** ¼ - ½ - ¾ or ⅓ - ⅔ - ⅞ configurations
- + **XO or OX 2-lite styles available**
- + **Double sash locks** provide extra security (2 locks standard at 27 ¼" or higher)
- + **Beveled exterior frame** makes a stylish design statement
- + **Factory applied wrap-around foam** enhances thermal efficiency around the frame's exterior
- + **Fusion-welded frame** and sash corners ensure frame durability
- + **Sloped sill** accommodates easy water run-off
- + **Factory-installed half screen** standard\*
- + **Head expander and sill angle** are included
- + **Jamb depth: 2.75"**
- + **Transferable limited lifetime warranty**



2-lite sliding window




3-lite sliding window

### CUSTOM Options

- + **Low-E Glass**
- + **Low-E Glass + Argon Gas**
- + **Ultra Low-E Glass + Argon Gas**
- + **Obscure glass**
- + **Double strength glass**
- + **Optional 5/8" or 1" contoured, 5/8" or 3/4" flat grids available**
- + **Custom sizes cut on 1/8" width and height**
- + **Factory mulling of twins and triples**
- + **Charcoal aluminum mesh screen\***
- + **Lifetime glass breakage warranty**

### + COLOR OPTIONS\*\*



[www.atrium.com](http://www.atrium.com)



Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory Sales Manager for details.



Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.  
\* Screens are not meant to restrain a child from falling through an open window.  
\*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors. REV 11/23